



www.selmi-group.com

AUTOMATIC DEMOULDER

Automatic demoulder for chocolate pralines and bars
Chocolate moulding machine

This machine is designed to carry out the automatic demoulding of pralines or bars that are held inside moulds

The production rate of this machine is 4 moulds per minute

It can, as an option, be loaded manually but it achieves a very high performance and productivity rate if combined with the SPIDER cooling tunnel. The moulds are automatically demoulded onto a rigid surface at the exit of the tunnel, hence avoiding manual intervention from the operator. The mat will carry the product to the wrapping machine or to the packaging line.

automatic demoulder



Technical data

Electrical specification: 220 V single phase - 50 Hz
Required power: 1.5 kW - 16 A - 3 poles
Optimal operating temperature: 20/25°C , maximum 32°C
Dimensions: h. 1300, w. 1900, d. 1100 mm
Needs to be connected to a compressed air source: 100 lt/min - minimum 6 bar - filtered, dry, deoiled



Belt & Bearings

Authorized Distributor in thailand

BELT AND BEARINGS CO.,LTD.

69/27 VIPAVADEE RANGSIT RD. SAMSANENAI, PAYATHAI, BANGKOK 10400

Tel 02-6449001-3

Email : Sales@Beltandbearings.com

www.beltandbearings.co.th