

filler pot

Pot filler

This machine is designed for the potting of spreadable creams of medium and high density and viscosity. The gear pump is built of alimentary grade aluminium and can inject at pressures of up to 4 atmospheres. The body of the pump can be completely dismantled and cleaned in just a few minutes and thus facilitates the changing of the cream to be potted. It is particularly suitable for clients who produce pastes and alimentary conserves of all types.

Tecnical data

Electrical specification: 400 V three phase 50 Hz
 Power required: 0,9 kW - 16 A - 5 poles
 Tank capacity: 6 Kg
 Hourly production rate: 50 Kg
 Dimensions: h. 700 mm, w. 380 mm, d. 380 mm



automatic filler pot

Automatic Pot filler

This machine is designed for the potting of spreadable creams of medium and high density and viscosity. The gear pump is built of alimentary grade aluminium and can inject at pressures of up to 4 atmospheres. The body of the pump can be completely dismantled and cleaned in just a few minutes and thus facilitates the changing of the cream to be potted. It is particularly suitable for clients who produce pastes and alimentary conserves of all types.

Tecnical data

Electrical specification: 400 V three phase 50 Hz
 Power required: 1,5 kW - 16 A - 5 poles
 Tank capacity: 6 Kg
 Hourly production rate: 50 Kg
 Dimensions: h. 700 mm, w. 380 mm, d. 380 mm

